



DECLARATION OF PERFORMANCE

Intended use	Solid fuel, top burning heating boilers
Unique identification codes	L-10, L-20, L-40, L-10u, L-20u, L-40u, L-10 Comfort, L-20 Comfort, L-40 Comfort, L-10u Comfort, L-20u Comfort, L-40u Comfort,
Manufacturer	UAB VAKARO RASA, Taikos str. 18, Trakiškis, LT-38102
System of AVCP	System 4
EU directives	Pressure Equipment Directive 97/23/EC
Harmonized Standards	EN 303-5: 2012, EN 12828:2012+A1:2014, EN 12171:2006, EN 14336:2004, EN 15378:2008
Notified body	TÜV Thüringen e.V., Certification Body 0090

Declared Performance

CHARACTERISTIC	DECLARED PERFORMANCE	HARMONISED STANDART
Tha max. pressure	2 bar	EN 303-5: 2012, EN 12828:2012+A1:2014, EN 12171:2006, EN 14336:2004, EN 15378:2008
Pressure Protection valve	1,5 bar	
The amount of water in the boilers L10, L10u, L10 Comfort, L10u Comfort	30 L	
The amount of water in the boilers L20, L20u, L20 Comfort, L20u Comfort	35 L	
The amount of water in the boilers L40, L40u, L40 Comfort, L40u Comfort	45 L	
Max. temperature	90 °C	
CO, using RUF high technology briquettes made of oak sawdust.	max 1040 mg/m ³ , accord to EURO 4 class	
Hard parts(dust), using RUF high technology briquettes made of oak sawdust.	max 68 mg/m ³ , accord to EURO 4 class	

The performance of the product is in conformity with the declared performance outline above. This Declaration of Performance is issued under the sole responsibility of the manufacturer identified above

Signed on behalf of the manufacturer by:
Director Valdas Krasauskas

Date

2017 06 12

